

FEATURES

- Drying area: 48cm width x 65cm length (heat spread gives slightly larger area.)
- Twelve medium wave quartz infrared elements with polished curved aluminium reflectors for efficient heat distribution.
- Filtered forced air cooling of circuitry, element reflectors and case, ideal for high temperature/ volume environments.
- Simple to use controls.
- Six selectable drying sections for power economy on a smaller print area.
- Flash power adjustable from 50 to 100% in 10% increments.
- Pre-heat power adjustable from 0 to 40% in 10% increments.
- Automatic shutdown of pre-heat to standby after period of inactivity, saves power and prevents overheating boards. Dryer comes out of standby when carousel starts or reset button is pressed.

RT4865M DRYER


- Continuous variable timer 2 to 10 seconds.
- Manual/ reset button for strike offs which functions even if input from sensor is present.
- Multifunction control socket, isolated input for either internal or external timed control, auxiliary 12vdc supply for external sensors/ switches etc. Comes standard with MHM control cable for carousel computer control.
- Over current and over temperature protection.
- In print station stand hanger to fit S-Type (510mm or wider, please specify width.)
- Epoxy coated, welded aluminium frame construction with aluminium panels results in strong light weight unit approx. 17kg easily moved and handled.

POWER REQUIREMENTS

- 3 Phase (380-400v) + Neutral + Earth - (breaker required size 25 to 30A.)
- Supplied with 32Amp 5pin plug, 1.5 metres, (M version) power supply cable, consumption max. (All elements on) $\pm 17\text{Kw}$

OPTIONS AVAILABLE

- Control input cables and sensors/switches/ interfaces for various auto and manual machines, (specify.)
- Longer/ shorter power supply cable, different power connector, (specify.)
- Crating for shipment.



REP-TECH
PTY LTD

Steve 083 225 9420

Dean 084 556 3538

www.reptech.co.za

steve@reptech.co.za

dean@reptech.co.za

Design & Manufacture of Dryer Systems