

FEATURES

- Drying area: 300mm x 250mm nominal (heat spread gives slightly larger area.)
- Automatic operation with sensor.
- Adjustable stand allowing side to side, angle and height setting.
- Built in pre-heat.
- Automatic shutdown of pre-heat to standby after period of inactivity, saves power and prevents overheating boards. Dryer comes out of standby when carousel starts or reset button pressed.
- Four medium wave infr-red elements and vented reflectors.
- Dual cooling fans and air intake filter.
- Manual button and graduated time setting control for strike offs 2 to 10 secs.

S4_e MINI DRYER WITH STAND

- Stackable to increase drying area (300mm x 500mm)*
- Second dryer socket for stackable function.
- Main cable 1.25Mtr.-connector IEC 309 16 A 2P + E.**

* Stackable two dryers in the 250mm dimension only, can be one behind each other giving 300mm left to right and 500mm back to front or side by side giving 500mm left to right and 300mm back to front (two on one stand).

** Nominal flash power 3.3Kw, 14.5A @ 230VAC, IEC 309 16A 2P+E connector recommended, no adapters or underrated extension leads to be used.

ADDITIONAL CHARGE OPTIONS AVAILABLE

- Longer mains supply cable.
- Different mains connectors.
- Crating for shipment.
- Stands and adapter frames for different machine makes.



REP-TECH
PTY LTD

Steve 083 225 9420
Dean 084 556 3538

www.reptech.co.za

steve@reptech.co.za
dean@reptech.co.za

Design & Manufacture of Dryer Systems